
	D-R164 684	THIN SUPI ACOUSTIC PHYSICS	ERCONDUCT: WAYES(U) M LEYY 2	ING FILM WISCONS D DEC 85	CHARAC' IN UNIV- AFOSR-1	TERIZATI -MADISON TR-86-00	ON BY S DEPT (07	SURFACE OF	1/1	
U	NCLASSIFIED	AFOSR-84	-0350				F/1	20/3	NL	
		,								
			END FILMED							
		_								



MICROCOPY RESOLUTION TEST CHART

REPORT DOCUMENTATION PAGE

TYPE OF HEPORT & PERIOD COVERED Research Progress Report 9-30-84 to 9-30-85 6 PERFORMING DIG. REPORT NUMBER

BEFORE COMPLETING FORM

8 CONTRACT OR GRANT NUMBER(S)

AFOSR 84-0350

10 PROGRAM ELEMENT, PROJECT, TASK AREA & WURK UNIT NUMBERS FERFORMING ORGANIZATION NAME AND ADDRESS University of Wisconsin-Milwaukee CellO2F Department of Physics 2306 Milwaukee, WI 53201 12 REPORT DATE

11 CONTROLLING OFFICE NAME AND ADDRESS Air Force Office of Scientific Research / NE Bolling AFB Building 410 Washington, D. C. 20332 MONITORING AGENCY NAME & ADDRESS'II different from Controlling Office)

12-20-85 NUMBER OF PASES

SECURITY CLASS (of this report)

Same as # 11

UNCLASSIFIED DECLASSIFICATION DOWNGRADING

16 DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17 DISTRIBUTION STATEMENT (of the abstract entered in Black 20, if different from Report)

Approved for public release; distribution unlimited.

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on severse side if necessary and identify by block number)

thin superconducting film surface acoustic wave SAW

Attenuation of surface acoustic

NbN film

renormalized dielectric function Kosterlitz-Thouless

flux line dipoles

ABST/RACT (Continue on roverse side if necessary and identify by block number)

Both the dc electrical resistivity and the attenuation of surface acoustic waves (SAW) were measured in the superconducting state of a granular lead film, when its sheet resistivity was 2000 Ω/sq and 3000 Ω/sq , sa a function of a perpendicular magnetic field. At 4.2 K the film appears to have an upper critical field of about 60 K Gauss. - mul page

DD FORM 1473 EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

19. Key Words - continued

superconducting states granular lead films sheet resistivity magnetic field upper critical field bulk ultrasonic measurements attenuation $Er_{1-x}^{Ho}x^{Rh}_{4}^{B}_{4}$ relaxation mechanism Ho ions

ferromagnetic superconductors

superconducting screening crystalline field effects spin phonon interaction acoustoelectric coupling granular Al film electron phonon interaction superconducting energy gap electron mean free path

vortex antivortex bound pairs

amorphous superconductor

effective energy gap strongly localized superconductor piezoelectric coupling granular films superconducting superlattice films magnetic superconductors transition metal superconductors renormalization

crystalline electric field ternary compounds Rayleigh waves submillikelvin temperatures dilution refrigerator automatic velocity and measuring apparatus submicron photolithography

system
Nb₃Sn
Nb₃Ge
He³ cryostat
amorphous molybdenum films
quartz substrates
lithium niobate substrates
interdigital electrodes

ErRh₄B₄
He³ probe
Cu₂Mo₆S₈
Va₃Sn

superlattice of Nb and Cu superlattice of Nb and Zr heavy fermion superconductor proximity effect superinsulated dewars pure Nb single crystal film weakly coupled superconductors

20. Abstract-continued

Bulk ultrasonic measurements have been made in the series ${\rm Er}_{1-x}{\rm Ho}({\rm Rh}_4^7{\rm B}_4^7)$. At 15 MHz a broad peak in attenuation, due to a relaxation mechanism associated with the Ho ions, is observed around 10 K. It moves to lower temperatures as x is decreased. An increase in attenuation is observed in the superconducting state of those alloys which are ferromagnetic superconductors. This increase may be due to superconducting screening of crystalline field effects which inhibit spin phonon interaction in the normal state.

Preliminary measurements of the acoustoelectric coupling of SAW with an Al granular film, which is held 15 @'s above the SAW, indicate that at 19 MHz the attenuation increases when the film becomes superconducting. This is an unexpected result since at this frequency the attenuation is expected to decrease when the film becomes superconducting.

film becomes superconducting.

The research goals and objectives of this investigation will remain the same. No significant reorientations are anticipated for the second and third years of this project.

AIR PORCE OFFICE OF SCIENTIFIC RESEARCH (AFSC: NOTICE OF TRANSMITTAL TO DTIC

This technical report has been reviewed and is approved for public release IAV AFR 190-13.

RESEARCH OBJECTIVES AND APPROACHES Distribution is unlimited.

within J. There

The objective of this investigation is to characterize than film superconductors with surface acoustic waves (SAW). By measuring the electron phonon interaction in thin films, the temperature dependence of the superconducting energy gap and the electron mean free path may be determined. It may also be possible to determine the existence of vortex antivortex bound pairs in amorphous superconductors and the effective energy gap in strongly localized superconductors. measuring the piezoelectric coupling to the sheet resistivity of granular films it may be possible to determine the size distribution of the granules and the distribution of the coupling between granules. Surface acoustic wave measurements of Josephson junction networks may be correlated with their signal processing properties. SAW measurements of superconducting superlattice films may provide information about the mechanical properties of these films. Measurements with bulk waves will provide information about spin phonon coupling in magnetic superconductors and electron phonon interaction in the transition metal superconductors.

ACCOMPLISHMENTS

Both the dc electrical resistivity and the surface acoustic wave (SAW) attenuation coefficient were measured in the superconducting state of a granular lead film as a function of an applied magnetic field normal to the film plane at several constant temperatures. Measurements were performed when the film had a sheet resistivity of, 2000 Ω/sq and 3000 Ω/sq . These different sheet resistivities were obtained by oxidizing the film in place. The initial sheet resistivity of the film was 1000 Ω/sq . Both sets of measurements

Approved for public release; distribution unlimited.

appear to indicate upper critical fields for this film of 60 K Gauss at 4.2 K.

We have evolved a theoretical model that takes into account renormalization to explain the experimental discrepancy in the superconducting state between the SAW attenuation in a NbN film and its sheet resistivity. The film has a BCS transition temperature of about 10 K, and a Kosterlitz-Thouless transition temperature of 5 K, and a normal state sheet resistivity of 30 Kg/sq. An exact solution has been found for the renormalized dielectric function of a two dimensional superconductor which has Kosterlitz-Thouless flux line dipoles.

Bulk ultrasonic measurements in the series of ferromagnetic superconductors $\text{Er}_{1-x}\text{Ho}_x\text{Rh}_4\text{B}_4$ with $x=1,\ 0.912,\ 0.813$, and 0.6 (received from Dr. Brian Maple, UCSD) appear to indicate that spin phonon interaction is supressed by crystalline electric fields but superconductivity screens these fields permitting the interaction to appear. This may be the reason for the increase in attenuation that we have observed in the superconducting state of these ternary compounds.

Measurements on a sample with x=0.295, in addition to the ones above, exhibit a maximum in attenuation centered around 10 K which moves down in temperature as x is decreased. This maximum may be associated with a relaxation process involving a ground state of the Ho ions. The x=0.295 sample also exhibits another broad maximum around 4 K which is similar to the one reported around 5 K on a polycrystalline sample with x=0.

Measurements of the attenuation produced by a granular Al film in close proximity above the path transversed by a surface acoustic wave

have been made at several frequencies between 19 MHz and 281 MHz. The sheet resistivity of the film is about $1000~\Omega/\text{sq}$. The coupling between the SAW and the film is through the acoustoelectric effect, namely the piezoelectric fields accompanying the SAW induce currents in the film which absorb energy thereby attenuating the SAW.

Preliminary measurements show that the attenuation of 19 MHz waves increase when the film becomes superconducting. This is an unexpected result. For Rayleigh waves the acoustoelectric effect is proportional to the sheet resistivity in this frequency range and therefore the attenuation associated with it should vanish when the film becomes superconducting. There are no observable changes for the higher frequencies at the superconducting transition. This indicates that the separation between the granular Al film and the substrate of the SAW device is around 15 μ 's, since a maximum effect is observed for a particular separation, $z_{\rm O}$, when the SAW frequency is such that $z_{\rm O} = \frac{\lambda}{4\pi}$.

An invited paper was presented at the Eighth International Conference on Internal Friction and Ultrasonic Attenuation in Solids held at the University of Illinois at Urbana-Champaign on June 3-6, 1985.

FORECAST

THE SECOND PROPERTY PROPERTY

The research goals and objectives of this investigation will remain the same. The number of graduate research assistants will be maintained at the same level. The rate of expenditure of funds is expected to continue at the proposed level. No significant reorientations are anticipated for the second and third years of this research.

When the equipment provided by DOD-URIP Grant No. 84-0221 is assembled it will be possible to carry out these measurements down to submillikelvin temperatures and up to frequencies of 4 GHz. The dilution refrigerator has been ordered from Oxford Instruments and is expected in a few days. The automatic velocity and attenuation measurement apparatus up to frequencies of 160 MHz has been received from Matec. A schematic and list of the equipment necessary to extend the frequency range up to 4 GHz has been designed in collaboration with Matec and is being assembled at UWM. A computer to interface with this equipment has been ordered. The 2850A illuminator and flow booth for the submicron photolithography system have been ordered.

Appess	ion F	or		
NTIS			K	
DTIC :	rab -			
Unann	ounced	ì		
Just1	ficati	en		
	ibuti labil Wasil	ity i	Codes	
Dist		i deliv Nation		
1.1	t			

PUBLICATIONS

Two papers are to appear in the <u>Proceedings on Materials and Mechanisms of Superconductivity</u> and three papers in the Journal de Physique. Two papers have been submitted to the Physical Review, and one paper to Phys. Rev. Letters.

- Ultrasonic Attenuation Measurement of Er_{1-x}Ho_xRh₄B₄, K. J. Sun,
 M. Levy, M. B. Maple and M. S. Torikachvili, <u>Proceedings on Materials and Mechanisms of Superconductivity</u>, (eds. K. A. Gschneider, Jr. and E. L. Wolf, North Holland Publishing Co. 1985) (to be published).
- 2. Detection of Bound Vortex-Antivortex Pairs in a Superconducting Thin Film by Surface Acoustic Waves, A. Schenstrom, M. Levy, H. P. Fredricksen and J. Gavaler <u>Proceedings on Materials and Mechanisms of Superconductivity</u>, (eds. K. A. Gschneider, Jr. and E. L. Wolf, North Holland Publishing Co. 1985) (to be published).
- Magnetic Field Dependence of the Ultrasonic Attenuation and
 Resistance of a Superconducting Granular Lead Film, J. Schmidt,
 A. Schenstrom and M. Levy, Journal de Physique (to be published).
- 4. Detection of Bound Vortex-Antivortex Pairs in a Superconducting
 Thin Film by Surface Acoustic Waves, A. Schenstrom, M. Levy, H.
 P. Fredricksen and J. Gavaler, Journal de Physique (to be published).
- 5. Surface Acoustic Wave Investigation of Superconducting Films, M. Levy, Journal de Physique (to be published).
- 6. Ultrasonic Atttenuation and the Resistive Transition in a Superconducting Granular Lead Film, M. Levy, J. Schmidt, A. Schenstrom, M. Revzen, A. Ron, B. Shapiro, and C. G. Kuper (submitted to Phys. Rev.).

- 7. Attenuation of Surface Acoustic Waves by Bound Vortex-Antivortex
 Pairs in a Superconducting Thin Film, A. Schenstrom, M. Levy,
 H. P. Fredricksen and J. Gavaler (submitted to Phys. Rev.).
- 8. Analytic Solution of the Renormalization Equations of the Kosterlitz-Thouless Transition", A. Schenstrom (submitted to Phys. Rev. Letters).

TECHNICAL PERSONNEL

In addition to the principal investigator, the following graduate students have worked and will be working on this grant. The university has supported some of them as part of their matching commitment.

Full Time:

Mr. Anders Schenstrom (Senior Graduate Research Assistant)
Theoretical renormalization model for acoustoelectric effect in superconducting

NbN, and SAW investigation of granular films

and superlattices.

Mr. Jeff Schmidt (Senior Graduate Research Assistant)

SAW investigation of granular Pb films and

amorphous films.

Mr. Keun-Jenn Sun (Senior Graduate Research Assistant)

Ultrasonic investigation of ternary ferromagnetic superconductors and pure

vanadium single crystals.

Mr. Roy Wiegert (Senior Graduate Research Assistant)

Responsible for assembling automatic

ultrasonic attenuation and velocity measuring

apparatus. (DOD-URIP Grant No. 84-0221)

Part Time:

Mr. Huges-Pierre Baum (Junior Graduate Research Assistant)

Will work on layered compounds, strong

coupled superconductors and Al5

superconductors.

Mr. Qiang Qian (Junior Graduate Research Assistant)

Will work on dilution refrigerator.

(DOD-URIP Grant No. 84-0221)

Mr. Dale Walikainen (Junior Graduate Research Assistant)

Will work on Josephson coupled

superconducting arrays.

Mr. Min Feng Xu (Junior Graduate Research Assistant)

Will work on single crystal vanadium, ternary

alloys and chevrel phase superconductors.

SCIENTIFIC INTERACTIONS

1. Nb₃Sn and Nb₃Ge Films

For our research, Dr. Robert Hammond, Stanford University, will attempt to deposit $\mathrm{Nb_3Ge}$ films on aluminum nitride substrates. He will also attempt to deposit $\mathrm{Nb_3Sn}$ and $\mathrm{Nb_3Ge}$ films on passivated lithium niobate substrates.

2. Ternary Alloys

Polycrystalline samples of $\mathrm{Ho_{x}Er_{1-x}Rh_{4}B_{4}}$ have been obtained from Professor Brian Maple, U.C. San Diego. These samples have a ferromagnetic transition temperature that is accessible with a $\mathrm{He^{4}}$ cryostat. Therefore, the interplay between ferromagnetism and superconductivity can be more easily investigated ultrasonically.

3. Amorphous Superconductors

We have obtained from Professor Ted Geballe and Robert Hammond, Stanford University, amorphous molybdenum films stabilized with a small amount of niobium, which were deposited on quartz and lithium niobate substrates. Interdigital electrodes will be deposited on the substrates and prelimninary measurements will be initiated.

4. Single Crystals of the Ternary Alloys

Continued discussions with Dr. David Hinks, Argonne National Laboratory, concerning the possibility of obtaining single crystals of the ternary alloys. The first crystals will be of $ErRh_4B_4$. These crystals will also be measured with the He³ probe.

5. Single Crystal of Cu₂Mo₆S₈

Correspondence with Dr. Renee Flukiger, Solid State Institute, Karlsruhe, concerning the possibility of obtaining a single crystal of $\text{Cu}_2\text{Mo}_6\text{S}_8$ was conducted. He has grown such a crystal and hopefully it will be sent to us for characterization.

6. Array of Josephson Coupled Superconductors

Discussions were held with Professor R. S. Newrock, University of Cincinnati, concerning the deposition of an array of Josephson coupled superconductors on a piezoelectric substrate.

Interdigital electrodes will then be evaporated on this substrate in order to investigate the array with surface acoustic waves in the 700 MHz frequency range.

7. Films of Va₃Sn

Discussions were initiated with Dr. John Gavaler, Westinghouse, about obtaining thin films which will be measured with surface acoustic waves. Two substrates covered with films have been obtained.

. Artifically Produced Superlattice

Discussions were initiated with Dr. Ivan Schuller, Argonne National Laboratories, about the possibility of obtaining superlattices made of Nb and Cu in order to investigate their characteristics with surface acoustics waves. Similar discussions were held with Professor Ted Gabelle and Dr. Robert Hammond, Stanford University, to obtain superlattice structures of Nb and Zr.

- 9. <u>1984 IEEE Ultrasonic Symposium</u>
 - On November 14-16 chaired session at the Dallas, Texas, conference.
- 10. <u>Visit to Physics Department, University of Illinois, Urbana</u>
 Champaign

Presented seminar on November 20, 1984

"Surface Acoustic Wave Investigation of Superconducting Films."

Discussed measurements on superconducting films with Professor Dan Ginsberg and measurements in the mixed superconducting state with Professor Andrew Granato. Visited the low temperature labs and discussed the installation of their dilution refrigerators because of the installation we were planning for our new refrigerator (DOD-URIP Grant No. 84-0221).

- 11. <u>During travel in Europe Professor Levy made visits to the</u>
 following:
 - 11.1 Visit to the Institute of Physical Chemistry, Polish Academy

 of Science, Warsaw Poland

On December 27, 1984 presented seminar on "Surface Acoustic Waves."

Visited the surface studies laboratory.

11.2 <u>Visit to Swiss Federal Institute (ETH) Zurich, Switzerland</u>
On January 4-5, 1985, visited the low temperature laboratory
and discussed the merits of the SHE and Oxford dilution
refrigerators installed at the labs there. Discussed with
Dr. Hans Rudi Ott his measurements on heavy fermion
superconductors and discussed with Dr. Ana Celia Mota her
measurements on the proximity effect at millikelvin

temperatures. Also discussed these topics with Professor Jorgen L. Olsen.

- 11.3 <u>Visit to the Bavarian Walther Meissner Low Temperature</u>

 <u>Laboratory, Munich, West Germany</u>

 On January 7 and 8, 1985, Professor Levy visited the Walther Meissner Low Temperature Laboratory and discussed with the director, Dr. Klaus Andres, the merits of their different large dilution refrigerators and the advisability of building specialized small dilution refrigerators in order not to require liquid nitrogen in their operation.
- 12. 1985 IEEE Ultrasonic Symposium

 Member of the program committee of the conference held in San

 Francisco on October 16-18, 1985.
- Attended the conference on March 25-29, 1985, which was held in Baltimore, Maryland and chaired a session on "Superconductivity: Al5 Compounds." Held discussions with Professor Ted Geballe, and Dr. Robert Hammond, Stanford University, concerning superlattices of Nb and Zr. Held discussions with Dr. John Gavaler about measuring some of their pure Nb single crystal films in order to establish a standard comparison with the Al5 superconducting films. Held discussions with Dr. George Crabtree, Argonne National Laboratory, about the single crystals of ErRh₄B₄ that they are attempting to grow at Argonne National Laboratory. Discussed with Professor R. Newrock his continuing attempts to make Josephson coupled arrays. They are going to use the

Cornell submicron facility to produce these arrays. Discussed with Dr. Ana Celia Mota the possibility of making surface acoustic wave measurements on systems which display the large superconducting proximity effect that she recently discovered. Continued discussions with Dr. Jim Smith, Los Alamos Laboratory, about the possibility of obtaining heavy fermion superconducting crystals from him for ultrasonic measurements. Discussed our bulk wave measurements on the ternary superconductors and our SAW measurements on granular superconductors with Dr. Lewis Testardi, National Bureau of Standards.

14. Materials and Mechanisms of Superconductivity Conference

Attended the conference on May 29-31, 1985, which was held in

Ames, Iowa. Presented two poster papers.

"Detecting Bound Vortex-Antivortex Pairs in a Superconducting Thin Film by Surface Acoustic Waves", A. Schenstrom, M. Levy, H. P. Fredricksen and J. Gavaler and

"Ultrasonic Attenuation Measurement of $Er_{1-x}Ho_xRh_4B_4$ ",

J. Sun, M. Levy M. B. Maple and M. S. Torikachvili

Discussed the results on the Kosterlitz-Thouless vortex

antivortex pairs with Art Hebard, Bell Labs. Discussed with

Allen Goldman, University of Minnesota, and Cornell Chun, Sperry

Computer Systems Division, the possibility of obtaining an array

of Josephson coupled superconductors deposited on a piezoelectric

substrate. The array would be made at Sperry. Discussed with

Brian Maple, UCSD, the possibility of obtaining single crystals

of $ErRh_4B_4$ that were sufficiently large for ultrasonic

measurements.

15. <u>Eight International Conference on Internal Friction and</u>
<u>Ultrasonic Attenuation in Solids</u>

Attended the conference on June 3-6, 1985 held in Urbana, Illinois. Presented an invited plenary paper

"Surface Acoustic Wave Investigation of Superconducting Films", M. Levy

and two contributed papers

"Magnetic Field Dependence of the Ultrasonic Attenuation and Resistance of a Superconducting Granular Lead Film",

J. Schmidt, A. Schenstrom and M. Levy

and

"Detection of Bound Vortex-Antivortex Pairs in a Superconducting Thin Film by Surface Acoustic Waves",

A. Schenstrom, M. Levy, H. P. Fredricksen and J. Gavaler

16. Gordon Research Conference on Superconducting Films

Attended conference on August 26-30, 1985 which was held in

Plymouth, New Hampshire. Presented an invited poster

Granular Pb Films", M. Levy

"Surface Acoustic Wave Investigation of Superconducting

Discussed with G. Deutcher, University of Tel Aviv, Art Hebard, Bell Labs, and H. Fink, University of California Davis, different models for explaining the magnetic field dependence of the attenuation of surface acoustic waves produced by superconducting granular lead films. Discussed with A. C. Mota, ETH-Zurich, the proximity effect at millikelvin temperatures and the type of information that ultrasonic measurements would yield about this effect. Discussed with P. Martinolli, University of Neuchatel,

the possibility of depositing a weakly coupled array of superconductors with a sheet resistivity of a few hundred ohms on a piezoelectric substrate in order to perform SAW measurements to determine if a correlation could be obtained between these measurements and those which have already been made on NbN films.

END

FILMED
3-86

DTIC